



Great Power Battery Co., Ltd

Title	Model	Description	Page
Product Specification	LFB AAA	Lithium/Iron Disulfide (Li/FeS ₂)	1

1. Preface

The purpose of this product specification is to provide technical information for the Lithium/Iron Disulfide (Li/FeS₂) Lithium battery LFB AAA, manufactured and supplied by Great Power battery Co., Ltd.

2. Description and Model

2.1 Description	Lithium/Iron Disulfide (Li/FeS ₂)
2.2 Model	LFB AAA

3. Specification

3.1 Rated Capacity	1100mAh at 350mA discharge
3.2 Average Weight	7.7g
3.3 Nominal Voltage	1.5V
3.4 Work Voltage	1.30V at Constant current 100mA discharge
3.5 Cut-off Discharge Voltage	0.80V
3.6 Max.Discharge Current	1000mA
3.7 Volume	3.8 cubic centimeters (0.2 cubic inch)
3.8 Lithium Content	Less than 0.5 gram (0.02 oz.) per cell
3.9 Ambient Temperature for Standard Charge for Discharge	-20 °C ~ 45 °C
3.10 Storage for within the temperature for within the humidity	-20 °C ~ 45 °C ≤75%
3.11 Energy Density Wh/L Wh/Kg	
3.12 Shell Life	10years
3.13 Charge State Internal Impedance	

4. Appearance

Appearance shall be free from any remarkable scratch, flaws, rust, discoloration or electrolyte leakage (visible or by smell)

5. Standard Test condition

5.1 Environment Conditions

Unless otherwise specified, all test stated in this Product Specification are conducted within the temperature 15~25 °C and the humidity 45~85%RH.



Great Power Battery Co., Ltd

Title	Model	Description	Page
Product Specification	LFB AAA	Lithium/Iron Disulfide (Li/FeS)	2

5.2 Test Equipment

(1) Impedance meter

The impedance meter with AC 1kHz should be used

6. Test Procedure and Its Standard

Item	Measuring Procedure	Standard
6.1 Appearance	Visual	No Defect and Leak
6.2 Dimension	Caliper	As item 8
6.3 Weight	Scale	As item 3.12
6.4 Max. Discharge Current	Until final discharge voltage	1000mA
6.6 Open Circuit Voltage	Measure open circuit voltage	>1.72V
6.7 Internal Impedance	Measure the battery with 1kHz AC	
6.8 Discharge Capacity	The battery discharge until final discharge voltage 0.8V, at 0.2C and measure the capacity	>1100mAh
6.9 Leakage Proof	The battery shall be stored at 40±2 °C and humidity 80±5% for 21 days	No leakage should be observed by visual inspection

7. Discharging at 350mA and 100mA to 0.8V

8. Dimension (Bare cell) mm

