



## SPECIFICATION

1. Rated Voltage ..... 1.5 VDC
2. Operating Voltage ..... 1~2 VDC
3. Max. Rated Current ..... 70mA/9VDC
4. Min. Sound Pressure Level ..... 85dB/10cm
5. Resonant Frequency ..... 2731Hz
6. Coil Resistance .....  $6.5 \pm 1 \Omega$
7. Coil Impedance .....  $22 \Omega$
8. Case Material ..... MPPO
9. Operating Temperature .....  $-20 \sim +70^{\circ}\text{C}$
10. Store Temperature .....  $-30 \sim +80^{\circ}\text{C}$
11. Weight ..... 2g

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				<b>Magnetic Buzzer</b>	
				<b>KP12-04B1</b>	
No.	DESCRIPTION	APPROVED	DATE		
<small>           TOLERANCES UNLESS NOTED OTHERWISE:            .X *            .XX *            .XXX *            90° FORMED ±2°            ANGLES ±1°            FIRST ANGLE PROJECTION         </small>		APPROVALS		DATE	
		DRAWN			
		CHECKED		UNIT	DWG. NO.
		APPROVED		mm	KP3.840.657
			05.04.08	SCALE	SHEET
				NOT TO SCALE	VER 1.1