



SPECIFICATION

- 1. Rated Voltage 1.5 V
- 2. Operating Voltage 1~2 V
- 3. Max. Rated Current 30mA
- 4. Coil Resistance $16 \pm 4 \Omega$
- 5. Coil Impedance 40Ω
- 6. Min. Sound Pressure Level $85 \pm 3 \text{dB}$
- 7. Resonant Frequency 2048Hz
- 8. Case Material ABS
- 9. Operating Temperature $-20 \sim +60^\circ\text{C}$
- 10. Store Temperature $-30 \sim +70^\circ\text{C}$
- 11. Weight 2g

				KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com	
				Magnetic Buzzer	
				KP12-185AL	
No.	DESCRIPTION	APPROVED	DATE		
TOLERANCES UNLESS NOTED OTHERWISE: .X * .XX * .XXX * 90° FORMED $\pm 2^\circ$ ANGLES $\pm 1^\circ$ FIRST ANGLE PROJECTION		APPROVALS			
		DRAWN	CHECKED		
		APPROVED	05.08.01	UNIT	DWG NO.
				mm	KP3.840.660
				SCALE	SHEET
				NOT TO SCALE	VER 1.0