



SPECIFICATION

- 1. Rated Voltage 1.5V
- 2. Operating Voltage 1~2V
- 3. Max. Rated Current 80mA
- 4. Coil Resistance $5.5 \pm 1 \Omega$
- 5. Coil Impedance $9.5 \pm 3 \Omega$
- 6. Min. Sound Pressure Level 85dB/10cm
- 7. Resonant Frequency 2731Hz
- 8. Case Material PBT
- 9. Operating Temperature $-20 \sim +70^\circ\text{C}$
- 10. Store Temperature $-30 \sim +80^\circ\text{C}$
- 11. Weight 1g

				KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com	
				Magnetic Buzzer KPM09-04B3	
No.	DESCRIPTION	APPROVED	DATE		
<small> TOLERANCES UNLESS NOTED OTHERWISE: .X * .XX * .XXX * 90° FORMED $\pm 2^\circ$ ANGLES $\pm 1^\circ$ FIRST ANGLE PROJECTION </small>		APPROVALS	DATE	UNIT	DWG. NO.
		DRAWN		mm	KP3.840.704
		CHECKED		SCALE	SHEET
		APPROVED	05.03.31	NOT TO SCALE	VER 1.1