



## SPECIFICATION

1. Rated Voltage ..... 1.5V
2. Operating Voltage ..... 1~2V
3. Max. Rated Current ..... 80mA
4. Coil Resistance .....  $5.5 \pm 1 \Omega$
5. Coil Impedance .....  $9.5 \pm 3 \Omega$
6. Min. Sound Pressure Level ..... 90dB/10cm
7. Resonant Frequency ..... 2731Hz
8. Case Material ..... PBT
9. Operating Temperature .....  $-20 \sim +70^\circ\text{C}$
10. Store Temperature .....  $-30 \sim +80^\circ\text{C}$
11. Weight ..... 1g

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				<b>Magnetic Buzzer</b>	
				<b>KPM09-04D</b>	
No.	DESCRIPTION	APPROVED	DATE		
<small>TOLERANCES UNLESS NOTED OTHERWISE: X * XX * XXX * 90° FORMED ±2° ANGLES ±1° FIRST ANGLE PROJECTION</small>		APPROVALS	DATE		
		DRAWN			
		CHECKED		UNIT	DWG. NO.
		APPROVED	05.08.19	mm	KP3.843.663
				SCALE	SHEET
				NOT TO SCALE	VER 1.0