



- **产品材质:** A.C.E 部位采用 UL 认可的尼龙 PA66, B.D 部位采用丁腈橡胶。
- **螺纹规格:** 公制(Metric), 德制(PG), 英制(G), 美制(NPT)。
- **工作温度:** 静态 -40℃ 至 100℃, 瞬时耐热至 120℃, 动态 -20℃ 至 80℃, 瞬间耐热至 100℃。
- **产品特性:** 特殊的夹紧爪与迫紧螺帽, 橡胶件设计, 可耐扭曲延长电缆寿命。夹紧电缆范围大, 抗拉力特强, 可防水, 防尘, 防盐, 耐酸碱, 酒精, 油脂及一般溶剂。
- **颜色种类:** 黑色(RAL9005)、浅灰(RAL7035)、银色(RAL7001), 特殊颜色可定做。

- **Material:** Parts A, C, E are made of UL approved nylon PA66, parts B and D are made of nitrile butadiene rubber (NBR).
- **Thread spec.:** Metric, PG, G, NPT.
- **Working temperature:** -40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃; -20℃ to 80℃ in dynamic state, instantaneous heat resistance up to 100℃.
- **Characteristics:** Special design of clamping die, sealing nut and rubber part, twisting resistance, prolonging cable life. Large range in clamping the cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.
- **Color:** Black(RAL9005), light grey (RAL7035), silver (RAL7001) as well as special colors that can be designed at request.

产品型号 Model	螺纹规格 Thread Size	适用电缆 Cable Range (mm)	螺纹外径 Thread O. D. L2 (mm)	螺纹长度 Thread Length L1 (mm)	扳手直径 Spanner Size A & E (mm)	数量 / 袋 Qty/bag
PG7-R	PG7	3~6.5	12.5	9	18/16	100
PG7-R	PG7	2~5	12.5	9	18/16	100
PG9-R	PG9	4~8	15.2	9	22/19	100
PG9-R	PG9	2~6	15.2	9	22/19	100
PG11-R	PG11	5~10	18.6	9	24/22	100
PG11-R	PG11	3~7	18.6	9	24/22	100
PG13.5-R	PG13.5	6~12	20.4	10	27/24	50
PG13.5-R	PG13.5	5~9	20.4	10	27/24	50
PG16-R	PG16	10~14	22.5	10	30/27	50
PG16-R	PG16	7~12	22.5	10	30/27	50
PG21-R	PG21	13~18	28.3	12	35/33	50
PG21-R	PG21	9~16	28.3	12	35/33	50

产品型号 Model	螺纹规格 Thread Size	适用电缆 Cable Range (mm)	螺纹外径 Thread O. D. L2 (mm)	螺纹长度 Thread Length L1 (mm)	扳手直径 Spanner Size A & E (mm)	数量 / 袋 Qty/bag
M12-R	M12x1.5	3~6.5	12	9	18/16	100
M12-R	M12x1.5	2~5	12	9	18/16	100
M16-R	M16x1.5	4~8	16	9	22/19	100
M16-R	M16x1.5	2~6	16	9	22/19	100
M18-R	M18x1.5	5~10	18	9	24/22	100
M18-R	M18x1.5	3~7	18	9	24/22	100
M20-R	M20x1.5	6~12	20	10	27/24	50
M20-R	M20x1.5	5~9	20	10	27/24	50
M22-R	M22x1.5	10~14	22	10	30/27	50
M22-R	M22x1.5	7~12	22	10	30/27	50
M25-R	M25x1.5	13~18	25	12	35/33	50
M25-R	M25x1.5	9~16	25	12	35/33	50
M27-R	M27x1.5	13~18	27	12	35/33	50
M27-R	M27x1.5	9~16	27	12	35/33	50