LED constant voltage waterproof switching power supply 80W

Features:

- ·Constant voltage style power supply
- ·170~264VAC AC input
- ·Small volume, low weight, high efficiency
- ·Protections: short circuit/over load/over voltage/over temp
- ·Cooling by free air convection
- ·Fully encapsulated with IP67 level
- ·100% full load burn-in test
- ·2Year warranty



LPV-80W				
Model		LPV-80-12	LPV-80-24	LPV-80-36
OUTPUT	DC voltage	12V	24V	36V
	Voltage tolerance	±1%	±1%	±1%
	Rated current	6.6A	3.3A	2.2A
	Current range	0~6.6A	0~3.3A	0~2.2A
	Rated power	79.2W	79.2W	79.2W
	Ripple&noise	100mvp-p	150mvp-p	150mvp-p
INPUT	Voltage range	90~264VAC,126~373VDC		
	Frequency	47~63Hz		
	AC current	2A/115VAC, 1A/230VAC		
	Efficiency	82%	84%	84%
	Inrush current	Cold start current 18A/115VAC, 36A/230VAC		
PROTECTION	Leakage current	<1mA/240VAC		
	Over load	Rated output power 115%~135% start over load protection		
		Protection type: hiccup mode, auto-recovery after fault		
		15.6~17.8V	condition is removed 30.6~33.2V	42.6~44.2V
	Over voltage			
		Protection type: hiccup mode, auto-recovery after fault condition is removed		
	Over temperature	Shell temp≥85°C, start over temperature protection		
		Protection mode: cutoff output, auto-recovery after		
	W/ - 1 ' (1 1'4-	temperature become normal -10°C~+60°C, 20%~90%RH		
ENVIRONMENT	Working temp, humidity			
	Storage temp.humidity Withstand vibration	-20°C~+85°C, 10%~95%RH non condensing 10~500HZ, 2G 10min/1cycle, period for 60minutes, each		
SAFETY		I/P-O/P: 1.5KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC		
	Withstand voltage Isolated resistance	I/P-O/P: 1.5KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC I/P-O/P: I/P-FG: 0.9KVAC		
FITSTANDARDS		Fit UL1012, IP67 protect level		
	Safety standard	<u> </u>		
OTHERS	EMC standard	Fit EN55022, CLASSA 185*69*43mm (L*W*H)		
	Dimension Weight/goodsig	0.9kg/20pcs/19kg/0.026 m ³ /0.91CUFT		
NOTE	Weight/packing 0.9kg/20pcs/19kg/0.026 m³/0.91CUFT 1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and			
	25°C of ambient temperature.			
	2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire			
	terminated with a 0.1uf & 47uf parallel capacitor.			
	3. Tolerance : includes set up tolerance, line regulation and load regulation.			