

MPH80E

Silicon Epitaxial Planar Switching Diode

Features


- High-speed
- High reliability

Applications

- Ultra high speed switching

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RM}	80	V
Reverse Voltage	V_R	80	V
Average Rectified Forward Current	$I_{F(AV)}$	100	mA
Peak Forward Current	I_{FM}	300	mA
Surge Current (1 μs)	I_{surge}	4	A
Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Max.	Unit
Forward Voltage at $I_F = 100\text{ mA}$	V_F	1.2	V
Reverse Current at $V_R = 70\text{ V}$	I_R	0.1	μA
Diode Capacitance at $V_R = 6\text{ V}$, $f = 1\text{ MHz}$	C_d	3.5	pF
Reverse Recovery Time at $I_F = 5\text{ mA}$, $V_R = 6\text{ V}$	t_{rr}	4	ns




SEMTECH ELECTRONICS LTD.
Subsidiary of Sino-Tech International (BVI) Limited




Dated : 15/06/2009


Capacitance




Reverse Recovery Time





Power Attenuation Curve



Forward Characteristics



REVERSE CHARACTERISTICS



SEMTECH ELECTRONICS LTD.
 Subsidiary of Sino-Tech International (BVI) Limited




MPH80E


PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-323



UNIT	A	b _p	C	D	E	H _E
mm	1.10 0.80	0.40 0.25	0.15 0.10	1.80 1.60	1.35 1.15	2.80 2.30



SEMTECH ELECTRONICS LTD.
Subsidiary of Sino-Tech International (BVI) Limited



Dated : 15/06/2009