


Technical characteristics <i>Caratteristiche tecniche</i>	L	Spanner <i>Chiave</i>		Panel drilling <i>Foratura pannello</i>	Cable Dia <i>Cavo Dia</i>	Thread <i>Filettatura</i>	Part No. <i>Codice</i>	Part No. <i>Codice</i>	Part No. <i>Codice</i>
		SW1	SW2						
	11	16	16	12.5	3 - 6,5	M 12x1,5	Black <i>Nero</i>	Light grey <i>Grigio chiaro</i>	Grey <i>Grigio</i>
	11	19	19	16.5	4 - 8	M 16x1,5	7000.7821.1	7000.7821.2	7000.7821.0
	10,2	24	24	20.5	6 - 12	M 20x1,5	7000.7822.1	7000.7822.2	7000.7822.0
	12	32	32	25.5	11 - 18	M 25x1,5	7000.7823.1	7000.7823.2	7000.7823.0
	14	35	35	32.5	12 - 21	M 32x1,5	7000.7824.1	7000.7824.2	7000.7824.0
	15	53	53	40.5	22 - 32	M 40x1,5	7000.7825.1	7000.7825.2	7000.7825.0
	16,5	60	60	50.5	30 - 38	M 50x1,5	7000.7826.1	7000.7826.2	7000.7826.0
	20	68	68	63.5	35 - 44	M 63x1,5	7000.7827.1	7000.7827.2	7000.7827.0
	11	16	16	12.7	3 - 6,5	Pg 7	7000.7828.1	7000.7828.2	7000.7828.0
	10,2	19	19	15.4	4 - 8	Pg 9	7000.7829.1	7000.7829.2	7000.7829.0
	10,2	22	22	18,8	5 - 10	Pg 11	7000.7830.1	7000.7830.2	7000.7830.0
	12	24	24	20,7	6 - 11	Pg 13.5	7000.7831.1	7000.7831.2	7000.7831.0
	12	27	27	22,8	9 - 13	Pg 16	7000.7832.1	7000.7832.2	7000.7832.0
	12	33	33	28,6	13 - 18	Pg 21	7000.7833.1	7000.7833.2	7000.7833.0
	14,5	42	42	37,4	17,5 - 25	Pg 29	7000.7834.1	7000.7834.2	7000.7834.0
	16,8	53	53	47,5	22 - 32	Pg 36	7000.7835.1	7000.7835.2	7000.7835.0
	16,8	60	60	54,5	32 - 38	Pg 42	7000.7836.1	7000.7836.2	7000.7836.0
	18	68	68	59,8	37 - 44	Pg 48	7000.7837.1	7000.7837.2	7000.7837.0
						7000.7838.1	7000.7838.2	7000.7838.0	

Technical characteristics

Caratteristiche tecniche



Thread:

Metric 1.5 pitch in accordance with EN 50262
 Pg in accordance with DIN 40430

IP Protection:

IP68 in accordance with EN 60529

Working temperature:

- 40°C ÷ + 100°C

Materials:

Body: Polyamide Pa 66 UL94 V2
 Gasket: NBR

Characteristics:

Special design of clamping die, sealing nut and rubber part, twisting resistance, prolonging cable life. Waterproof, dustproof and high resistance to salt, acid, alkali, alcohol, grease and general solvent.

Applications:

For sealed enclosures and boxes.

Color:

Grey RAL 7001, light grey RAL 7035 or black RAL 9005



Filettatura:

Metriche passo 1,5 secondo EN 50262
 Pg secondo DIN 40430

Grado di protezione IP:

IP68 secondo EN 60529

Limiti di temperature:

- 40°C ÷ + 100°C

Materiali:

Corpo: Poliammide Pa 66 UL94 V 2
 Guarnizione: NBR

Caratteristiche:

Particolare progetto del sistema di chiusura, del sistema di tenuta e della guarnizione. Aumenta la durata del cavo. Resistente all'acqua, alla polvere, all'ambiente salino, agli acidi, agli alcali, all'alcool, ai grassi ed ai comuni solventi.

Applicazioni:

Per custodie e cassette stagne.

Colore:

Grigio RAL 7001, grigio chiaro RAL 7035 o nero RAL 9005