

LT 455(450).W SERIES

Part Number	Center Frequency (KHz)	Insertion Loss (dB)	PassBand Ripple (dB) max	6dB Bandwidth (KHz) min	50dB Bandwidth (KHz) min	Stop Band Att. ± 10 KHz (dB) min	I/O Impedance (Ω)
LT450BW	450 ± 2.0	4	2	± 15	± 30	40	1500
LT455BW	455 ± 2.0	4	2	± 15	± 30	40	1500
LT450CW	450 ± 2.0	4	2	± 12.5	± 24	40	1500
LT455CW	455 ± 2.0	4	2	± 12.5	± 24	40	1500
LT450DW	450 ± 1.5	4	2	± 10	± 20	40	1500
LT455DW	455 ± 1.5	4	2	± 10	± 20	40	1500
LT450EW	450 ± 1.5	6	2	± 7.5	± 15	40	1500
LT455EW	455 ± 1.5	6	2	± 7.5	± 15	40	1500
LT450FW	450 ± 1.5	6	2	± 6	± 12.5	40	2000
LT455FW	455 ± 1.5	6	2	± 6	± 12.5	40	2000
LT450GW	450 ± 1.5	6	2	± 4.5	± 10	40	2000
LT455GW	455 ± 1.5	6	2	± 4.5	± 10	40	2000
LT450HW	450 ± 1.0	6	2	± 3	± 9	40	2000
LT455HW	455 ± 1.0	6	2	± 3	± 9	40	2000
LT450IW	450 ± 1.0	6	2	± 2	± 7.5	40	2000
LT455IW	455 ± 1.0	6	2	± 2	± 7.5	40	2000
LT450HTW	450 ± 1.0	6	2	± 3	± 9	60	2000
LT455HTW	455 ± 1.0	6	2	± 3	± 9	60	2000

