

TCXO 36

Temperature Compensated Crystal Oscillator



Specification

Model	TCXO36
Frequency Range, MHz	1.0 ~ 40.0
Demensions, mm	36.1x27.2x16.0
Supply Voltage, VDC	+3.3, +5.0, +9.0, +12.0
Frequency Stability vs Temp.	See Table 1
Supply current	See Table 2
Operating Temp, °C	See Table 1
Storage Temp, °C	-40 ~ +100
Frequency Stability vs Loas	±0.1ppm Max vs ±10% load change
Frequency Accuracy, ppm	±1.0 max
Aging, PPM	±0.5 year max
Package	Bulk

Output Waveform & Load Characteristic

Output Waveform	Output Characteristics	Option Code
Clipping Sine Wave	Load: 10K /10pF Output level: >1Vp-p Current: 4mA Max Load: Max 10 low power consumption TTL gates "1" level: >+2.4VDC	01
TTL	"0" level: <+0.2VDC Duty Cycle: 40/60 Rise/fall time: <6ns Current: 20mA Max Load: max 10 low power consumption TTL/HCMOS	02
HCMOS	"1" level: >+4.5VDC "0" level: <+0.5VDC Duty Cycle: 40/60 Rise/fall time: <6ns Current: 20mA Max Load: max 10 low power consumption TTL/ACMOS	03
ACMOS	"1" level: >+4.5VDC "0" level: <+0.5VDC Duty Cycle: 40/60 Rise/fall time: <6ns Current: 20mA Max	04

Table 2

Application

- SDH/SONET
- ATM
- WLL
- Mesasurement Equipment

Features

- Wide Freq. Range up to 40.0MHz
- Low Aging
- TTL, HCMOS, ACMOS, Clipping Sing Wave, Sing Wave

Standart Frequencies

Standart Frequencies in MHz

7.000000	9.600000
7.280000	10.00000
9.000000	40.00000
9.100000	

Other frequencies available. Please consult our sales office.

Frequency Stability vs Temperature

Frequency Stability Temp Range

±0.3ppm max	0°C ~ +50°C
±0.5ppm max	0°C ~ +70°C
±1.0ppm max	-20°C ~ +70°C
±1.5ppm max	-30°C ~ +75°C
±2.0ppm max	-40°C ~ +85°C

Table 1

Trough hole Dimension, mm

