

REV	CONTENT	CHK	DATE
V0.0	CONTENT	ZCL	25.09.29

Electrical :

	UL	IEC
1.Rated Voltage :	300V	160V
2.Rated Current :	8A	8A
3.Wire Range:	22-16AWG	0.34-1.5mm ²
4.Stripping Length :	9-10mm	
5.Operating Temperature :	-40℃~+115℃	
6.RoHS Compliance		
7."★" is the key quality control point		

GT212D - 3.81 -02P - 1 3 - 00

① ② ③ ④ ⑤ ⑥

① Sereies NO. ④ 1 Single Pitch
2 Double Pitch

② Pitch ⑤ Color: 1 Grey
③ Poles 2 Blue
02 02Contacts 3 Black
04 04Contacts 4 Green
... 5 Orange
36 36Contacts 6 Red
7 Transparent
8 Yellow
9 White

⑥ Customer Request: 00--Standard

4	SHRAPNEL	XX	2	STAINLESS STEEL	/
3	CONTACTS	XX	2	Copper alloy	Tin Plated
2	BUTTON	XX	2	POM(White)	UL94-HB
1	HOUSING	XX	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	ZCL	DATE	25.09.29	SIZE	A4 UNITS mm SHEET/OF 1 / 1
CHK.		DATE		SCALE	1:1
APP.		DATE		NAME	GT212D-3.81-02P-13-00
				DWGNO.	XXXX

Grolten 宁波冠泰电子有限公司
NINGBO GOLTEN ELECTRONICS CO., LTD.

