



NOTES

- (1) PART NO. : 224-1C ANODE-CATHODE
- (2) CONTACT MATERIAL: 0.3MM THICK BRASS NICKEL PLATED
- (3) SPRING MATERIAL:  $\varnothing 0.5$ MM SPRING STEEL NICKEL PLATED
- (4) PROCESS CORNER R=0.30MM
- (5) TOLERANCE: ISO 2768-M, UNLESS OTHERWISE SPECIFIED
- (6) SURFACE NO BURRS, NO GREASE
- (7) RoHS COMPLIANT

3			COMFORTABLE ELECTRONIC CO.LTD.			
2						
1						
NO.	MODIFICATION	DATE	NAME	BATTERY CONTACT:224-1C ANODE-CATHODE		
			SCALE	1:1	APPD	
General Tolerances			UNIT	MM	CHKD	
0 ~ >3	$\pm 0.10$	30 ~ >120	$\pm 0.30$	The Third Angle Projection	MAT'L	SEE NOTES
3 ~ >6	$\pm 0.10$	120 ~ >400	$\pm 0.50$		DATE	DEC. 23. 2020
6 ~ >30	$\pm 0.20$	Angle: $\pm 3^\circ$			DR NO	D <sub>2</sub> -2241C-1220