



**SPECIFICATION**

- (1) ITEM NO. : CH274-2450LF
- (2) HOUSING MATERIAL: LCP+30%GF UL 94V0 WHITE COLOR
- (3) CONTACT MATERIAL: PHOSPHOR BRONZE 0.15MM THICKNESS  
GOLD 1U" PLATED OVER Ni 50U" MIN
- (4) CURRENT RATING: 2A (AC/DC)
- (5) VOLTAGE RATING: 500V (AC/DC)
- (6) CONTACT RESISTANCE: 30 MILLIOHMS
- (7) INSULATION RESISTANCE: 500 MEGAOHMS
- (8) TEMPERATURE RANGE: -55°C TO +85°C
- (9) HUMIDITY: 40°C AND 90~95% RH FOR 96 HOURS
- (10) RoHS COMPLIANT

1. Changed these size: from 7.0mm to 7.1mm from 36.4mm to 36.1mm from 33.4mm to 33.3mm from 3.5mm to 3.3mm 2. Add the DIM 1.6mm & 1.8mm		FEB/11/2015		<b>COMFORTABLE ELECTRONIC CO.LTD.</b>		
Changed the size from 3.24mm to 2.70mm		FEB/11/2015				
<b>NO.</b>	<b>MODIFICATION</b>	<b>DATE</b>	<b>NAME</b>	COIN CELL HOLDER: CH274-2450LF		
			<b>SCALE</b>	2:1	<b>APPD</b>	
<b>General Tolerances</b>			<b>UNIT</b>	MM	<b>CHKD</b>	
0~>3	±0.10	30~>120	±0.30	<b>MAT'L</b>	SEE SPEC	<b>DWN</b> Rao xianhui
3~>5	±0.10	120~>400	±0.50	<b>DATE</b>	MAY. 12. 2017	<b>DR NO</b> CH274-0517C
6~>30	±0.20	Angle: ±3°		The Third Angle Projection		