



Model	TA01B	TA02B	TA03B	TA05B (4.5 x 4.5mm)	TA06B (6 x 6mm)
Rating	DC 12V 50mA	DC 12V 50mA	DC 12V 50mA	DC 12V 50mA	DC 12V 50mA
Insulation Resistance	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)
Dielectric Strength	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min
Contact Resistance	100 mΩ Max	100 mΩ Max	100 mΩ Max	100 mΩ Max	100 mΩ Max
Electrically Life	300000 cycles	50000 cycles	50000 cycles	300,000 cycles	300,000 cycles
Operating Temperature Range	-10°C ~ +60°C	-10°C ~ +60°C	-10°C ~ +60°C	-25°C ~ +70°C	-25°C ~ +70°C
Operating Force (OF)	160 ± 30g	130 ± 30g	130 ± 30g	160 ± 50g	160 ± 50g
Actuator Length	H: 0.8 1.2	H: 4.3 5	H: 4.3 5	H: 4.3 5 7 9.5 12	H: 4.3 5 7 9.5 12
Applications	TV sets. VCRs communication	TV sets. VCRs communication	TV sets. VCRs communication	TV sets. VCR etc	TV sets. VCR etc



Model	TA06BR	KT11	TA13B	TA14B (Double Action)	TA15B (Water Proof)
Rating	DC 12V 50mA	DC 12V 50mA	DC 30V 20mA	DC 30V 20mA	DC 30V 30mA
Insulation Resistance	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 100V)
Dielectric Strength	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min
Contact Resistance	100 mΩ Max	100 mΩ Max	100 mΩ Max	200 mΩ Max	50 mΩ Max
Electrically Life	300,000 cycles	100000 cycles	100000 cycles	10000 cycles	10000 cycles
Operating Temperature Range	-25°C ~ +70°C	-25°C ~ +70°C	-20°C ~ +70°C	-20°C ~ +70°C	-40°C ~ +85°C
Operating Force (OF)	160 ± 50g	160 ± 50g	160 ± 50gf	F1:100 ± 40 F1:60 ± 40 F2:250 ± 80 F2:150 ± 80	130 ± 40 gf
Actuator Length	H:3.15 3.85 5.85 11.35		H: 2.6 3.4	H: 1.1mm/1.8mm	H: 4.7
Applications	TV sets. VCR etc	TV sets. VCR etc	TV sets. VCR etc	vidio camera. VCR	microwave ovens



Model	TA16B	TA17B	TA12B	KS01-A	KS01-B
Rating	DC 12V 50mA	DC 30V 20mA	DC 12V 50mA	DC 35V 10mA	DC 35V 10mA
Insulation Resistance	100 MΩ Min (DC 250V)	100 MΩ Min (DC 100V)	100 MΩ Min (DC 100V)	100 MΩ Min (DC 250V)	100 MΩ Min (DC 250V)
Dielectric Strength	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min	AC 250V for 1 min
Contact Resistance	100 mΩ Max	100 mΩ Max	100 mΩ Max	30 mΩ Max	30 mΩ Max
Electrically Life	10000 cycles	10000 cycles	100000 cycles	100000 cycles	100000 cycles
Operating Temperature Range	-25°C ~ +70°C	-20°C ~ +70°C	-20°C ~ +70°C	-20°C ~ +70°C	-20°C ~ +70°C
Operating Force (OF)	130 ± 30 gf	F1:100 ± 40 F1:60 ± 40 F2:250 ± 80 F2:150 ± 80	160 ± 30 g	130 ± 50g	130 ± 50g
Actuator Length	H: 0.8 ± 0.2	H: 7	H: 4.3 7.3 12		
Applications	TV sets. VCR etc	communications office	TV sets. VCRs etc	TV sets. VCRs etc	TV sets. VCRs etc

