



## SPECIFICATION

1. Rated Voltage .....6VDC
  2. Operating Voltage .....4~8VDC
  3. Max. Rated Current .....15mA at 6VDC
  4. Resonant Frequency .....4.8±0.5KHz
  5. Min. Sound Pressure Level.....85dB at 6VDC/30cm
  6. Tone Nature .....Continuous
  7. Shell Material .....PBT
  8. Operating Temperature .....-20~+80℃
  9. Store Temperature .....-30~+100℃
  10. Weight .....6g
- Red(红).....Positive(+)  
 Black(黑).....Negative(-)

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
		<b>Piezo Buzzer</b>			
		<b>KPI-2210L-06</b>			
No.	DESCRIPTION	APPROVED	DATE		
TOLERANCES UNLESS NOTED OTHERWISE .X * .XX * .XXX * 90° FORMED +2° ANGLES ±° FIRST ANGLE PROJECTION		APPROVALS	DATE	UNIT	DWG NO.
		DRAWN		mm	KP3.840.067
		CHECKED			
		APPROVED	05.02.29	SCALE	SHEET
					VER 1.2