



## SPECIFICATION

1. Rated Voltage .....6VDC
  2. Operating Voltage .....4~8VDC
  3. Max. Rated Current .....15mA at 6VDC
  4. Min. Sound Pressure Level.....85dB at 6VDC/30cm
  5. Resonant Frequency .....3.7±0.5KHz
  6. Tone Nature.....Continuous
  7. Shell Material/Color.....ABS/White
  8. Operating Temperature .....-20 ~ +60°C
  9. Store Temperature .....-30 ~ +70°C
  10. Weight .....8g
- Red(红).....Positive(+)  
 Black(黑).....Negative(-)

				<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
No.		DESCRIPTION	APPROVED	DATE	
<small>TOLERANCES UNLESS NOTED OTHERWISE          X ±          .XX ±          .XXX ±          90° FORMED ±15°          ANGLES ±1°</small>		APPROVALS		DATE	
		DRAWN			
		CHECKED			UNIT
FIRST ANGLE PROJECTION		APPROVED	04.09.15		DWG NO. <b>KP3.840.071</b>
		SCALE		NOT TO SCALE	SHEET
				VER	1.1