

A

A

B

B

C

C

D



D

E

E

F

F



## SPECIFICATION

- 1.Rated Voltage ..... 12VDC
- 2.Operating Voltage ..... 3~20VDC
- 3.Max.Rated Current ..... 12mA at 12VDC
- 4.Resonant Frequency ..... 2.8±0.5KHz
- 5.Min.Sound Pressure Level..... 98dB at 12VDC/30cm
- 6.Tone Nature ..... Continuous
- 7.Shell Material ..... ABS/Black
- 8.Operating Temperature ..... -20~+60°C
- 9.Store Temperature ..... -30~+70°C

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				<b>Piezo Buzzer</b> <b>KPI-4000P</b>	
No.		DESCRIPTION	APPROVED	DATE	
TOLERANCES UNLESS NOTED OTHERWISE		APPROVALS		DATE	
X XX XXX 90° FORMED +2° ANGLES -1°		DRAWN			
FIRST ANGLE PROJECTION		CHECKED			
APPROVED		05.08.01		SCALE	SHEET
				VER	1.0
UNIT		DWG NO.	KP3.840.130		
mm					