



SPECIFICATION

- 1. Rated Voltage12VDC
- 2. Operating Voltage3~24VDC
- 3. Max. Rated Current80mA
- 4. Resonant Frequency 3.2 ± 0.5 KHz
- 5. Min. Sound Pressure Level..... 103 ± 3 dB/100cm/12VDC
- 6. Tone NatureContinuous
- 7. Shell Material/ColorPC/Black
- 8. Operating Temperature-20~+110°C
- 9. Store Temperature-30~+120°C
- 10. Weight12.5g
- Red(红).....Positive(+)
- Black(黑).....Negative(-)

| | | | | | |
|--|-------------|-----------|------|---|----------------|
| | | | | KEPO NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD http://www.chinaacoustic.com | |
| | | | | Piezo Buzzer KPI-4020L | |
| No. | DESCRIPTION | APPROVED | DATE | | |
| <small>TOLERANCES UNLESS NOTED OTHERWISE X ± .XX ± .XXX ± 90° FORMED ±1° ANGLES ±1°</small> | | APPROVALS | | DATE | |
| | | DRAWN | | | |
| <small>FIRST ANGLE PROJECTION</small> | | CHECKED | | | |
| | | APPROVED | | 04.09.15 | |
| | | | | UNIT | DWG NO. |
| | | | | mm | KP3.840.146.01 |
| | | | | SCALE | SHEET |
| | | | | NOT TO SCALE | VER 1.1 |