



SPECIFICATION

1. Rated Voltage 12 VDC
 2. Operating Voltage 3~20 VDC
 3. Max. Rated Current 20mA at 12VDC
 4. Min. Sound Pressure Level 90dB at 12VDC/30cm
 5. Resonant Frequency 2.8 ± 0.5 KHz
 6. Tone Nature Slow Pulse
 7. Case Material ABS
 8. Operating Temperature $-20 \sim +60^{\circ}\text{C}$
 9. Store Temperature $-30 \sim +70^{\circ}\text{C}$
 10. Weight 13g
- Red(红) Positive(+)
 Black(黑) Negative(-)

				KEPO NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD http://www.chinaacoustic.com	
				Piezo Buzzer KPI-4213	
No.	DESCRIPTION	APPROVED	DATE		
<small>TOLERANCES UNLESS NOTED OTHERWISE X ± XX ± XXX ± 90° FORMED ±15° ANGLES ±1°</small>		APPROVALS		DATE	
		DRAWN			
<small>FIRST ANGLE PROJECTION</small> 		CHECKED		UNIT	DWG NO.
		APPROVED		mm	KP3.840.102
			04.09.15	SCALE	SHEET
				NOT TO SCALE	VER 1.1