



Tone	Connection
Slow Pulse	A Connect With Negative
Fast Pulse	A Connect With Megutive C Connect With B
Continuous	B Connect With Megutive

SPECIFICATION

- Rated Voltage12VDC
- Operating Voltage6~28VDC
- Max.Rated Current20mA at 12VDC
- Min.Sound Pressure Level90dB at 12VDC/30cm
- Tone NatureContinuous+Fast Pulse+Slow Pulse
- Resonant Frequency2.9±0.5KHz
- Case MaterialABS/Black
- Operating Temperature-20~+60°C
- Store Temperature-30~+70°C
- Weight36g

				KEPO NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD http://www.chinaacoustic.com	
No.	DESCRIPTION	APPROVED	DATE	Piezo Buzzer	
TOLERANCES UNLESS NOTED OTHERWISE		APPROVALS		KPI-4353	
.X ±		DRAWN	DATE	UNIT	DWG NO.
.XX ±		CHECKED		mm	KP3.840.124
.XXX ±		APPROVED	04.02.07	SCALE	SHEET
90° FORMED ±2°				NOT TO SCALE	VER 1.0
ANGLES ±1°					
FIRST ANGLE PROJECTION					