



## SPECIFICATION

1. Rated Voltage .....12VDC.
2. Operating Voltage .....3~16VDC.
3. Max. Rated Current .....35(20)mA at 12VDC
4. Min. Sound Pressure Level.....100(92)dB at 12VDC/30cm
5. Tone Nature .....Continuous+Slow Pulse
6. Resonant Frequency .....3.2±0.5KHz.
7. Shell Material/Color.....ABS/White
8. Operating Temperature .....-20~+60℃.
9. Store Temperature .....-30~+70℃ .
10. Weight .....21g.
11. Remark:
  - Black .....Ground(-)
  - Red .....Continuous(+)
  - Yellow ..... Slow Pulse(-)

				<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
No.	DESCRIPTION	APPROVED	DATE	Piezo Buzzer KPI-4513L	
<small>TOLERANCES UNLESS NOTED OTHERWISE</small> X ± XX ± XXX ± 90° FORMED +2° ANGLES -1°		APPROVALS	DATE		
		DRAWN		UNIT	DWG NO.
<small>FIRST ANGLE PROJECTION</small> 		CHECKED		mm	KP3.840.065
		APPROVED		03.03.27	SCALE
		SHEET		VER	1.0