



Specifications

- 1.Rated Voltage.....3.6V
- 2.Operating Voltage.....2-6V
- 3.Max. Rated Current.....200mA
- 4.Coil Resistance..... $5.5 \pm 1 \Omega$
- 5.Coil Impedance..... $9.5 \pm 3 \Omega$
- 6.Min. Sound Pressure Level.....90dB/10cm
- 7.Resonant Frequency.....3200Hz
- 8.Case Material.....PBT
- 9.Operating Temperature.....-20~ + 70°C
- 10.Store Temperature.....-30 ~ + 80°C
- 11.Weight.....1g

TOLERANCES UNLESS NOTED OTHERWISE .X ± .XX ± .XXX ± 90° FORMED +2° ANGLES -1°	DESIGN		KEPO MODEL NO.	CUSTOMER		
	CHECKED		KPM09-04C	CUSTOMER NO.		
	APPROVED					
	DATE	04.02.20	DWG NO.	VER	1.0	SCALE
	CONTRACT NO.		KP3.840.738.02	UNIT	mm	SHEET
FIRST ANGLE PROJECTION	AGENCY APPROVAL		NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD http://www.chinaacoustic.com			

△			
△			
△			
△			
NO.	DATE	REVISION	REFERENCE DWG