



## SPECIFICATION

1. Rated Voltage .....12Vp-p Square Wave
2. Max. Allowable Voltage .....30Vp-p Square Wave
3. Max. Rated Current .....2mA at 3.5KHz/12Vp-p Square Wave
4. Min. Sound Pressure Level.....80dB at 3.5KHz/12Vp-p Square Wave/10cm
5. Resonant Frequency .....3.5±0.5KHz
6. Capacitance at 120Hz.....15000pF ±30%
7. Case Material.....ABS
8. Operating Temperature .....-20~+60°C
9. Store Temperature .....-30~+70°C
10. Weight .....2.5g

				<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				Piezo Transducer KPR-2320	
No.	DESCRIPTION	APPROVED	DATE	UNIT DWG NO.	
TOLERANCES UNLESS NOTED OTHERWISE: X = .XX = .XXX = 90° FORMED ±2° ANGLES ±1°		APPROVALS		mm KP3.840.355	
FIRST ANGLE PROJECTION		CHECKED		SCALE	SHEET
		APPROVED	03.08.01		VER 1.0