



SPECIFICATION

1. Rated Voltage.....12Vp-p Square Wave
2. Max. Allowable Voltage.....30Vp-p Square Wave
3. Max. Rated Current :.....3mA at 1.0KHz/12Vp-p Square Wave
4. Min. Sound Pressure Level:.....78dB at 1.0KHz/12Vp-p Square Wave/30cm
5. Resonant Frequency 1.0±0.5KHz
6. Capacitance at 120Hz.....50000pF±30%
7. Case Material.....ABS
8. Operating Temperature.....- 20~ + 60°C
9. Store Temperature.....- 30 ~ +70°C
10. Weight.....5g

				KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com	
No.	DESCRIPTION	APPROVED	DATE	Piezo Transducer KPR-3510GC	
<small> TOLERANCES UNLESS NOTED OTHERWISE: X * XX * XXX * 90° FORMED ±2° ANGLES ±1° FIRST ANGLE PROJECTION </small>		APPROVALS	DATE		
		DRAWN		UNIT	DWG NO.
		CHECKED		mm	KP3.840.338
		APPROVED	05.04.04	SCALE	SHEET
				NOT TO SCALE	VER 1.0