



## SPECIFICATION

1. Rated Voltage .....12Vp-p Square Wave
2. Max. Allowable Voltage .....30Vp-p Square Wave
3. Max. Rated Current .....4mA at 1.0KHz/12Vp-p Square Wave
4. Min. Sound Pressure Level.....78dB at 1.0KHz/12Vp-p Square Wave/30cm
5. Capacitance at 120Hz .....85000pF±30%
6. Resonant Frequency .....1.0±0.5KHz
7. Case Material .....ABS
8. Operating Temperature .....-20~+60°C
9. Store Temperature .....-30~+70°C
10. Weight .....10g

			<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>		
No.	DESCRIPTION	APPROVED	DATE	Piezo transducer KPR-4410G	
<small>TOLERANCES UNLESS NOTED OTHERWISE</small> X ± XX ± XXX ± 90° FORMED +2° ANGLES -1°		APPROVALS	DATE		
		DRAWN		UNIT	DWG NO.
<small>FIRST ANGLE PROJECTION</small> 		CHECKED		mm	KP3.840.341
		APPROVED		SCALE	SHEET
			03.06.06	NOT TO SCALE	VER 1.0