



## SPECIFICATION

1. Rated Voltage.....12Vp-p Square Wave
2. Max. Allowable Voltage.....30Vp-p Square Wave
3. Max. Rated Current.....4mA at 1.0KHz/ 12Vp-p Square Wave
4. Min. Sound Pressure Level.....70dB at 1.0KHz/12Vp-p  
.....Square Wave/10cm
5. Capacitance at 120Hz.....8000±30% pF
6. Resonant Frequency.....1.0±0.5KHz
7. Case Material.....ABS
8. Operating Temperature.....-20~+60°C
9. Store Temperature.....-30~+70°C
10. Weight.....4g

				<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				Piezo Buzzer KPR-5010	
No.	DESCRIPTION	APPROVED	DATE		
<small>TOLERANCES UNLESS NOTED OTHERWISE X = ± .XX = ± .XXX = ± 90° FURNISHED +2° ANGLES -1° FIRST ANGLE PROJECTION</small>		APPROVALS		DATE	
		DRAWN			
		CHECKED		UNIT	DWG NO.
		APPROVED		mm	KP3.840.331
			03.05.08	SCALE	SHEET
				NOT TO SCALE	VER 1.1