



## SPECIFICATION

1. Rated Voltage .....3Vp-p Square Wave
2. Max. Allowable Voltage .....25Vp-p Square Wave
3. Max. Rated Current .....2mA at 2.0KHz/3Vp-p Square Wave
4. Min. Sound Pressure Level.....70dB at 2.0KHz/3Vp-p Square Wave/10cm
5. Resonant Frequency .....2.0±0.5KHz
6. Capacitance at 100Hz.....34000pF ±30%
7. Material/Color .....PBT+30%玻纤
8. Operating Temperature .....-20~+70℃
9. Store Temperature .....-40~+80℃
10. Weight .....2g

△			
△			
△			
△			
NO.	DATE	REVISION	REFERENCE DWG

TOLERANCES UNLESS NOTED OTHERWISE .X ± .XX ± .XXX ± 90° FORMED +2° ANGLES -1° FIRST ANGLE PROJECTION 	DRAWN		KEPO MODEL NO.	CUSTOMER			
	DESIGN		KPT-1712	CUSTOMER NO.			
	CHECKED		DWG NO.	VER	1.0	SCALE	
	APPROVED		KP3.840.255	UNIT	mm	SHEET	
	DATE	03.07.31	<b>KEPO CO., LTD.</b> TEL:(+86)574-88370330 FAX:(+86)574-88370329				
CONTRACT NO.							
AGENCY APPROVAL							