



## Specifications

1. Rated Voltage.....3Vrms Sine Wave
2. Operating Voltage.....30Vp-p Sine Wave
3. Max. Rated Current.....2mA at 2.0KHz/3Vrms Sine Wave
4. Min. Sound Pressure Level.....75dB at 2.0KHz/3Vrms Sine Wave/10cm
5. Resonant Frequency.....2.0±0.5KHz
6. Capacitance .....30 nF ±30% at 100Hz
7. Housing Material/Color.....ABS/Black
8. Operating Temperature.....-20~+80℃
9. Store Temperature.....-30~+100℃
10. Weight.....3g

				<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
No.	DESCRIPTION	APPROVED	DATE	Piezo Transducer KPT-2311	
<small>TOLERANCES UNLESS NOTED OTHERWISE X = .XX = .XXX = 90° FORWARD +2° ANGLES -1° FIRST ANGLE PROJECTION</small>		APPROVALS	DATE		
		DRAWN		UNIT	DWG NO.
	CHECKED			mm	KP3.840.211
	APPROVED		03.08.23	SCALE	SHEET
				NOT TO SCALE	VER 1.3