



## SPECIFICATION

1. Rated Voltage .....9Vp-p Square Wave
2. Max. Allowable Voltage .....30Vp-p Square Wave
3. Max. Rated Current .....3mA at 2.0KHz/9Vp-p Square Wave
4. Resonant Frequency .....2.0±0.5KHz
5. Min. Sound Pressure Level.....78dB at 2.0KHz/9Vp-p Square Wave/10cm
6. Capacitance at 100Hz .....30000pF±30%
7. Shell Material/Color .....PA/Black
8. Operating Temperature .....-20~+70°C
9. Store Temperature .....-30~+80°C
10. Weight .....2.5g

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
No.		DESCRIPTION	APPROVED	DATE	Piezo Transducer <b>KPT-2320D</b>
TOLERANCES UNLESS NOTED OTHERWISE: X .X * XX .X * XXX .X * 90° FORMED ±2° ANGLES ±1° FIRST ANGLE PROJECTION			APPROVALS	DATE	
			DRAWN		UNIT mm DWG NO. KP3.840.291
			CHECKED		SCALE SHEET VER 1.2
			APPROVED	05.04.11	