



## SPECIFICATION

1. Rated Voltage.....9Vp-p Square Wave
2. Max. Allowable Voltage.....30Vp-p Square Wave
3. Max. Rated Current.....2mA at 2.8KHz/9Vp-p Square Wave
4. Min. Sound Pressure Level.....90dB at 2.8KHz/9Vp-p Square Wave/10cm
5. Resonant Frequency.....2.8±0.5KHz
6. Capacitance at 100Hz.....25000pF±30%
7. Operating Temperature.....-20~+60°C
8. Store Temperature.....-30~+70°C
9. Weight.....3g

				<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
		APPROVALS		Piezo Transducer KPT-2328BP	
No.	DESCRIPTION	APPROVED	DATE	UNIT	DWG NO.
TOLERANCES UNLESS NOTED OTHERWISE .X ± .XX ± .XXX ± 90° FORMED ±2° ANGLES ±°		CHECKED		mm	KP3.840.289
FIRST ANGLE PROJECTION		APPROVED	04.02.05	SCALE	SHEET
				NOT TO SCALE	VER 1.0