


A 螺帽 Lock Nut  
B 平垫 Washer  
C 主体 Body  
D 防水圈 Seal  
E 铁圈 Iron Washer  
F 迫紧螺帽 Sealing Nut



■ 产品材质: A.C.F 部位采用 UL 认可的尼龙 PA66, B.D 部位采用丁腈橡胶, E 部位采用铁皮。

■ 螺纹规格: 公制(Metric), 德制(PG), 英制(G), 美制(NPT)。

■ 工作温度: 静态 -40℃ 至 100℃, 瞬时耐热至 120℃, 动态 -20℃ 至 80℃, 瞬间耐热至 100℃。

■ 产品特性: 特殊的夹爪与迫紧螺帽, 橡胶件设计, 夹紧电缆范围大, 抗拉力特强, 可防水, 防尘, 防盐, 耐酸碱, 酒精, 油脂及一般溶剂。

■ 颜色种类: 黑色(RAL9005)、浅灰(RAL7035)、银色(RAL7001), 特殊颜色可定做。

■ Material: Parts A, C, F are made of UL approved nylon PA66, parts B and D are made of nitrile butadiene rubber (NBR), and part E are made of iron sheet.

■ Thread spec.: Metric, PG, G, NPT.

■ Working temperature: -40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃; -20℃ to 80℃ in dynamic state, instantaneous heat resistance up to 100℃.

■ Characteristics: Special design of clamping die, sealing nut rubber part, large range in clamping the cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.

■ Color: Black(RAL9005), light grey (RAL7035), silver (RAL7001) as well as special colors that can be designed at request.

产品型号 Model	螺纹规格 Thread Size	适用电缆 Cable Range (mm)	螺纹外径 Thread O. D. L2 (mm)	螺纹长度 Thread Length L1 (mm)	扳手直径 Spanner Size A & F (mm)	数量 / 袋 Qty/bag
ML12	M12x1.5	5~7	12	8	19/13	100
ML12	M12x1.5	3~5	12	8	19/13	100
ML16	M16x1.5	5~9	16	8	22/16	100
ML16	M16x1.5	3~6	16	8	22/16	100
ML18	M18x1.5	7~11	18	8	24/19	100
ML18	M18x1.5	5~8	18	8	24/19	100
ML20	M20x1.5	8~12	20	9	26/21	100
ML20	M20x1.5	6~9	20	9	26/21	100
ML22	M22x1.5	11~15	22	11	30/23	100
ML22	M22x1.5	7~12	22	11	30/23	100
ML25	M25x1.5	12~18	25	11	33/29	100
ML25	M25x1.5	7~13	25	11	33/29	100
ML28	M28x1.5	15~20	28	11	36/30	100
ML28	M28x1.5	11~16	28	11	36/30	100
ML30	M30x1.5	18~25	30	11	37/35	50
ML30	M30x1.5	15~22	30	11	37/35	50
ML32	M32x1.5	18~25	32	11	37/35	50
ML32	M32x1.5	15~22	32	11	37/35	50
ML36	M36x1.5	22~27	36	11	46/40	50
ML36	M36x1.5	17~22	36	11	46/40	50
ML40	M40x1.5	26~33	40	13	52/50	20
ML40	M40x1.5	20~27	40	13	52/50	20
ML46	M46x1.5	26~33	46	13	56/50	20
ML46	M46x1.5	20~27	46	13	56/50	20
ML50	M50x1.5	30~38	50	14	65/55	20
ML50	M50x1.5	23~31	50	14	65/55	20
ML63	M63x1.5	40~44	63	14	70/60	20
ML63	M63x1.5	32~36	63	14	70/60	20