Plastic threaded plug PG/M-T type

TÜV CE SGS IP68



- **材料**: 采用 UL 认可的尼龙 PA66
- **O- 密封件**: 丁腈橡胶
- **工作温度**: -40℃至 100℃
- **颜色种类**: 黑色(RAL9005)、浅灰(RAL7035)、银色(RAL7001), 特殊颜色可定做。

- Material: Made of UL approved nylon PA66.
- O-sealing element: Made of nitrile butadiene rubber (NBR).
- Working temperature: -40℃to100℃.
- Color: Black(RAL9005), light grey (RAL7035), silver(RAL7001) as well as special colors that can be designed at request.

产品型号 Model	螺纹规格 Thread Size	螺纹外径 Thread O. D. L2 (mm)	螺纹长度 Thread Length L1 (mm)	主体尺寸 Main body Dimensions L (mm)	盖帽尺寸 Cover Dimensions D (mm)
PG7-T	PG7	12.5	8.5	12.5	15
PG9-T	PG9	15.2	8.5	13	19
PG11-T	PG11	18.6	9	13	22
PG13.5-T	PG13.5	20.4	9	13	25
PG16-T	PG16	22.5	10.5	15	27
PG21-T	PG21	28.3	10.5	15.5	33
PG29-T	PG29	37	11.5	16	44
PG36-T	PG36	47	13.5	18	55
PG42-T	PG42	54	13.5	18.5	62
PG48-T	PG48	59.3	14.5	19.5	68

产品型号 Model	螺纹规格 Thread Size	螺纹外径 Thread O. D. L2 (mm)	螺纹长度 Thread Length L1 (mm)	主体尺寸 Main body Dimensions L (mm)	盖帽尺寸 Cover Dimensions D (mm)
M12-T	M12x1.5	12	8.5	12.5	15
M16-T	M16x1.5	16	8.5	13	19
M18-T	M18x1.5	18	9	13	22
M20-T	M20x1.5	20	9	13	25
M22-T	M22x1.5	22	10.5	15	27
M25-T	M25x1.5	25	10.5	15.5	29
M27-T	M27x1.5	27	10.5	15.5	33
M28-T	M28x1.5	28	10.5	15.5	33
M32-T	M32x1.5	32	10.5	16	38
M40-T	M40x1.5	40	11.5	18	46
M50-T	M50x1.5	50	13.5	18	56
M63-T	M63x1.5	63	14	19	68