

Clamp The Stopper Rod



Product material:	Made of EPDM material.
Color category:	Metallic
Installation method:	The stopper is placed in the aperture, and then the pressing screw cap can be.
Scope of application:	With SY cable fixed head use.

Technical specifications

Unit:mm

Order No	Outside diameter			Length C mm	Length C mm
	A mm	B mm	B1 mm		
S-055A	11	5.5	8.7	18	100
S-067	9.5	6.7	7.2	18	100
S-071	13.2	7	10.7	18	100
S-079	11	7.9	8.7	18	100
S-092	15.5	9.2	12.7	18	100
S-103	13.5	10.3	10.7	18	100
S-105	17	10.5	14.3	18	100
S-118	17	11.8	14.3	18	100
S-120	15.5	12	12.7	18	100
S-140	17	14	14.4	18	100
S-158	22	15.8	19.3	18	50
S-178	22	17.8	19.3	18	50
S-215	28	21.5	25	18	50
S-245	28	24.5	25	18	50
S-262	35	26.2	33	20	10
S-306	36	30.6	33	20	10
S-333	45	33.3	43.1	20	10
S-410	46	41	43.1	20	10
S-473	53	47.3	51.6	20	10
S-515	54.5	51.5	-	20	10



Technical specifications

Unit:mm

Black Order No.	Outside diameter		Length C mm	Packing pcs
	A mm	B mm		
SM-023	3	2.3	15	100
SM-026	3.6	2.6	15	100
SM-030	4	3	15	100
SM-032	4.2	3.2	15	100
SM-034	4.4	3.4	15	100
SM-037	4.7	3.7	15	100
SM-041	5.1	4.1	15	100
SM-050	6	5	15	100
SM-053	6.3	5.3	15	100
SM-060	7.5	6	15	100
SM-070	8.5	7	15	100
SM-073	8.5	7.3	15	100
SM-080	9.5	8	15	100
SM-090	10.5	9	15	100
SM-100	11.5	10	15	100

