## Compact single switching power supply 350W

## Features:

·AC input voltage range selected by switch

·Small volume, low weight, high efficiency

Protections: short circuit/over load/over voltage/over temp

·Cooling fan ON-OFF auto control

·LED indicator for power on

·100% full load burn-in test

·2 Year warranty



HS-350W					
Model		HS-350-5	HS-350-12	HS-350-15	HS-350-24
Output	DC voltage	5V	12V	15V	24V
	Voltage tolerance	±2%	±1%	±1%	±1%
	Rated current	50A	29A	23A	14.6A
	Current range	0~50A	0~29A	0~23A	0~14.6A
	Rated power	250W	348W	345W	350.4W
	Ripple&noise	150mvp-p	150mvp-p	150mvp-p	180mvp-p
	DCvoltage	-9%~+10%	±10%	±10%	±10%
Input	Voltage range	90~132VAC/180~264VAC(selected by switch), 255~373VDC			
	Frequency	47~63Hz			
	AC current	6.5A/115VAC, 4.0A/230VAC			
	Efficiency	80%	82%	82%	84%
	Inrush current	Cold start current 25A/115VAC, 50A/230VAC			
Protection	Leakage current	< 3.5mA/240VAC			
	Overload	Rated output power110%~135% start over load protection			
		protection type: hiccup mode, auto-recovery after fault			
		condition is removed			
	Over voltage	6.8~8.2V	15.6~17.8V	18.6~20.8V	30.6~33.2V
		Protection type: hiccup mode, auto-recovery after fault			
		condition is removed			
	Over temperature	TSW1detect on heatsink of power transistor≥85°C±5°C, start			
		over temperature protection			
		protection type: hiccup mode, auto-recovery after			
		temperature become normal			
Environment	Working	-10℃~+60℃, 20%~90%RH			
	<u> </u>	$-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$ , $10\% \sim 95\%$ RH non-condensing			
	Withstand vibration	10~500HZ, 2G 10min/1cycle, period for 60 minutes, each			
Safety	Withstand voltage	I/P-O/P: 1.5KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC			
	Isolated resistance	I/P-O/P,I/P-FG,O/P-FG: 100M ohms/500VDC			
Fitstandard	Safety standard	Fit UL1012			
	EMC standard	meet EN55022, CLASSA			
Others	Dimension	199*99*48mm (L*W*H)			
	Weight/packing	0.8kg/24pcs/20kg/0.034 m <sup>3</sup> /1.2CUFT			
Note	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load				
	and 25°C of ambient temperature.				
	2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-				
	wire terminated with a 0.1uf & 47uf parallel capacitor.				
	3. Tolerance: includes set up tolerance, line regulation and load regulation.				