

## LED constant voltage waterproof switching power supply 12W(New)

### Features:

- Constant voltage style power supply
- 170~264VAC AC input
- Small volume, low weight, high efficiency
- Protections: short circuit/over load/over voltage/over te
- Cooling by free air convection
- Fully encapsulated with IP67 level
- 100% full load burn-in test
- 1 Year warranty



LPV-12W-N				
Model		LPV-12N-12	LPV-12N-24	LPV-12N-36
OUTPUT	DC voltage	12V	24V	36V
	Voltage tolerance	±1%	±1%	±1%
	Rated current	1A	0.5A	0.33A
	Current range	0~1A	0~0.5A	0~0.33A
	Rated power	12W	12W	11.9W
	Ripple&noise	120mvp-p	150mvp-p	150mvp-p
INPUT	Voltage range	170~264VAC, 235~373VDC		
	Frequency	47~63HZ		
	AC current	0.1A/230VAC		
	Efficiency	78%	80%	82%
	Inrush current	Cold start current 30A/230VAC		
	Leakage current	<0.5mA/240VAC		
PROTECTION	Over load	Rated output power 105%~135%start over load protection Protection type: hiccup mode, auto-recovery after fault condition is removed		
	Over voltage	15.6~17.8V	30.6~33.2V	42.6~44.2V
	Over temperature	when temperature of transistor inner node is over 150℃, start over temperature protection Protection mode: cutoff output, auto-recovery after temperature become normal		
ENVIRONMENT	Workingtemp,humidity	-10℃~+60℃, 20%~90%RH		
	Storage temp,humidity	-20℃~+85℃, 10%~95%RH non condensing		
SAFETY	Withstand vibration	10~500HZ, 2G 10min/1cycle, period for 60minutes, each		
	Withstand voltage	I/P-O/P: 1.5KVAC I/P-FG:		
	Isolated resistance	I/P-O/P: 100M ohms/500VDC		
FITSTANDARDS	Safety standard	Fit UL1012, IP67 protect level		
	EMC standard	Fit EN55022, CLASSA		
OTHERS	Dimension	128*32*22mm (L*W*H)		
	Weight/packing	0.15kg/120pcs/19kg/0.027m³/0.95CUFT		
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature.			
	2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.			
	3. Tolerance : includes set up tolerance, line regulation and load regulation			