


Material:NYLON 66UL94V-O
 Accept 150G1-TP TERMINAL
 Current rating:1A AC,DC
 Voltage rating:100V AC,DC
 Contact resistance:30mΩMax
 Insulation resistance: 500MΩMin AC/Minute
 Temperature range:-25°C to +85°C

Poles	Part No.	Dimension mm (in.)	
		A	B
2	150G1-H02	4.50	1.50
3	150G1-H03	6.00	3.00
4	150G1-H04	7.50	4.50
5	150G1-H05	9.00	6.00
6	150G1-H06	10.50	7.50
7	150G1-H07	12.00	9.00
8	150G1-H08	13.50	10.50
9	150G1-H09	15.00	12.00
10	150G1-H10	16.50	13.50
11	150G1-H11	18.00	15.00
12	150G1-H12	19.50	16.50
13	150G1-H13	21.00	18.00
14	150G1-H14	22.50	19.50
15	150G1-H15	24.00	21.00

Rev	Description/Date	Drawn By: Storm.li	Customer:	Third angle projection	 X± .X±0.30 .XX±0.15 .XXX±0.08
△		Checked By:Simmon	Part No.: 150G1-HXX	General Dimension Tolerance	
△		Approved By: Tony	Title: Housing	Units: mm	
SGS Report No.: CE/2005/63004C					