


SEC.A-A

Dimensional and Ordering Information

Poles	Part No.	A	B
2	200B1R-H02	2.00	6.20
3	200B1R-H03	4.00	7.20
4	200B1R-H04	6.00	9.20
5	200B1R-H05	8.00	11.20
6	200B1R-H06	10.00	13.20
7	200B1R-H07	12.00	15.20
8	200B1R-H08	14.00	17.20
9	200B1R-H09	16.00	19.20
10	200B1R-H10	18.00	21.20
11	200B1R-H11	20.00	23.20
12	200B1R-H12	22.00	25.20
13	200B1R-H13	24.00	27.20
14	200B1R-H14	26.00	29.20
15	200B1R-H15	28.00	31.20
16	200B1R-H16	30.00	33.20

NOTE:

1. Housing Material: Nylon 66 UL94V-0
2. Insulation resistance: 1,000M ohm/min.
3. Withstanding voltage: 800V AC/minute.
4. Current rating: 3A AC/DC.
5. Voltage rating: 100V AC/DC

Rev	Description/Date	Drawn By: Storm.li	Customer:	Third angle projection	 X.± .X±0.30 .XX±0.20 .XXX±0.10
△		Checked By: Simmon	Part No.: 200B1R-HXX	General Dimension Tolerance	
△		Approved By: Tony	Title: 2.00mm Board-in type Housing	Units: mm	
SGS Report No.:					