

Specifications


Electrical

- Voltage Rating: 100V(AC)
- Current Rating: 1A
- Contact Resistance: 20mΩ max.
- Dielectric Withstandeing Voltage: 800V AC/1min.
- Insulation Resistance: 1000MΩ min.

Material

- Circuits: 2~15
- Insulator: Nylon 66 UL 94V-0
- Color: Brown
- Temperature Range: -25° C~+85° C
- Applicable PC Board Thickness: 0.8 to 1.6mm

Poles	Part No.	Dimension mm (in.)	
		A	B
2	200G1-H02	2.00	5.60
3	200G1-H03	4.00	7.60
4	200G1-H04	6.00	9.60
5	200G1-H05	8.00	11.60
6	200G1-H06	10.00	13.60
7	200G1-H07	12.00	15.60
8	200G1-H08	14.00	17.60
9	200G1-H09	16.00	19.60
10	200G1-H10	18.00	21.60
11	200G1-H11	20.00	23.60
12	200G1-H12	22.00	25.60
13	200G1-H13	24.00	27.60
14	200G1-H14	26.00	29.60
15	200G1-H15	28.00	31.60

Rev	Description/Date	Drawn By: Storm.li	Customer:	Third angle projection 	X± .X±0.30 .XX±0.20 .XXX±0.10
△		Checked By: Simmon	Part No.: 200G1-HXX		
△		Approved By: Tony	Title: 2.00mm pitch Housing		
SGS Report No.: CE/2005/63004C					