



- NOTES:**
- ELECTRICAL:**
- VOLTAGE RATING : 125 VAC RMS.
 - CURRENT RATING : 1.5 AMP.
 - CONTACT RESISTANCE : 35 MILLIOHMS MAX.
 - INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
 - DIELECTRIC STRENGTH : 1000 VAC RMS 60HZ, 1MIN.
- MECHANICAL:**
- HOUSING MATERIAL : POLYESTER OR HIGH TEMP. UL94V-0.
 - CONTACT MATERIAL : PHOSPHOR BRONZE t=0.35mm.
 - PLATING : 1: CONTACT AREA- SELECTIVE GOLD PLATING.
2: TAILS- 150u" TIN-LEAD MIN OVER 50u" NICKEL.
 - OPERATING LIFE : 750 CYCLES MIN.
 - PCB RETENTION PRE-SOLDER : 1 LB MIN.
 - PCB RETENTION POST-SOLDER: 10 LBS MIN.
- ENVIRONMENTAL:**
- STORAGE : -40°C TO +85°C.
 - OPERATION: 0°C TO 70°C.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

PRODUCT NUMBER:
210B-6X X B 0-R

1 2 3

- No. of Contact
66:6P6C
64:6P4C
62:6P2C

- Contact Plating
C:5u" Gold Plating
- Latch
B: Button Latch

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANGLES	ANG.	±5°
LINEAR	0, 0.0	±0.3, ±0.25
SCALE	0.00	±0.20

AS SHOWED UNIT: mm

DRAWN **Willis** 2012/08/03

CHECKED **Angel** 2012/08/03

APPROVED **Ken** 2012/08/03



www.attend.com.tw

DRAWN NAME:
Plastic Jack Single Port

PRODUCT NO. 210B-6XCBO-R

FILE NAME 210B-6XCBO-R_B_1

REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME
1			4			A4	1.0	
			5					
			6					
			7					
			8					
			9					
			10					