


SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000M Ω min
- Temperature Range : - 25°C to + 85°C

HOUSING

- Part No. : 254G4-HXX
- Poles: 2-25
- Material : PBT 94V-0 BLACK

Part No	Dimension		Part No	Dimension	
	A	B		A	B
254G4-H02	2.54	5.08	254G4-H14	33.02	35.56
254G4-H03	5.08	7.62	254G4-H15	35.56	38.10
254G4-H04	7.62	10.16	254G4-H16	38.10	40.64
254G4-H05	10.16	12.70	254G4-H17	40.64	43.18
254G4-H06	12.70	15.24	254G4-H18	43.18	45.72
254G4-H07	15.24	17.78	254G4-H19	45.72	48.26
254G4-H08	17.78	20.32	254G4-H20	48.26	50.80
254G4-H09	20.32	22.86	254G4-H21	50.80	53.34
254G4-H10	22.86	25.40	254G4-H22	53.34	55.88
254G4-H11	25.40	27.94	254G4-H23	55.88	58.42
254G4-H12	27.94	30.48	254G4-H24	58.42	60.96
254G4-H13	30.48	33.02	254G4-H25	60.96	63.50

Rev	Description/Date	Drawn By: Storm.li	Customer:	Third angle projection 			Units: mm		
\triangle		Checked By: Simmon	Part No.:	254G4-HXX			General Dimension Tolerance		
\triangle		Approved By: Tony	Title:	Housing			X.X ± 0.25	X.XX ± 0.1	X.XXX ± 0.08
SGS Report No.:									