


Accessories for actuator/sensor receptacles – male flange with wires, front-mounted



Typecode M08A04MBRF8WV005011
ID 1009020000017

Technical Data*

Connector A	
Connector	M8, A-coding
Number of Pins	4-Pin
Contacts	Brass, Gold-plated
Flange housing	Brass, Nickel-plated
Mounting type	Front-mounted
Contact Carriers	PA
Seal	FKM
Screw-in thread	M8 x 0.5
Connection mode	Crimp connection
Mechanical lifespan	≥ 100 Mating cycles
Pollution degree	III
Protection Class	IP67, (screwed together)
Cable length	0.5 m
Core insulation	PVC
Core cross-section	3 x 0.25 mm ²
Core colors	1-BN, 2-WH, 3-BU, 4-BK
Locking mode	Screw
Standard	IEC 61076-2-104

Electrical properties at +20 °C

Rated Voltage	50 V AC/60 V DC
Rated current	3 A
Insulation resistance	≥ 100 MΩ


Mechanical and chemical properties

Ambient temperature range (stationary) -40 °C ... 105 °C


Features

- M8, Male, 4Pin
- Resistant to salt spray
- Protection Class: IP67
- RoHS-compliant
- Approval: cULus, CE

Contact assignment




Connection diagram



Technical Data***Commercial data**

Country of origin	CN
Packaging unit	1 pc

Through bore

* Please note that the data specified here were design data, and the parameters of product are subject to changes without prior notice. Matters not mentioned herein. Please contact customer service. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.