


- NOTE:
1. Connector: Nylon
 2. Pin: Brass 4u" Gold Plated
 3. Temperature Rating: $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$.
 4. Current Rating: 10A
 5. Breakdown Voltage: 2KV/1Minute Moist
 6. Insulation Resistance: $10\text{M}\Omega, 500\text{VDC}$
 7. Contact Resistance: $10\text{m}\Omega$
 8. Waterproof: IP68



2	Blue
1	Brown
Conn.	Wire Color
Pin Out	

Pin Assignments
Front View 前視圖

Material List			
No.	Material No.	Q'ty	Material Description
1	501-00062-00	3	O-Ring $\phi 13 \times \phi 9, 0 \times \phi 2, 0$ Silicon Gel
2	104-00145-00	3	Connector 2Pin, Nylon+GF
3	107-00036-00	3	Nut-02 (blue)
4	801-00044-02	6	ZH1.5 Brass 4u" Gold Plated
5	903-00078-00	1	PCB 1*3, series FR-4, 94-V0
6	601-00040-00		Molding, Nylon (black) CHOGORI
7	502-00010-00	1	Gasket
8	109-00004-00	1	103 Seals Nut

UNIT:mm		Description M15 Distributor 1*3 In Series	
TOLERANCE		SCALE: N/A	SHEET 1 OF 1
.X	± 0.25	REV. D1	SIZE A4
.XX	± 0.15	* :Inspection Item	
.XXX	± 0.05		
ANGLES	$\pm 1^{\circ}$		

CHOGORI

PART NO 48002010-02	DRAWN BY XuXianMing	DATE 20140514
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.