


NOTE:
 1. Connector: Nylon
 2.Pin: Brass 4u" Gold Plated
 3.Temperature Rating:-40°C ~ +80°C.
 4.Current Rating:10A
 5.Breakdown Voltage:2KV/1Minute Moist
 6.Insulation Resistance:10MΩ,500VDC
 7.Contact Resistance:10mΩ
 8.Waterproof:IP68



| | |
|-------|------------|
| 2 | Blue |
| 1 | Brown |
| Conn. | Wire Color |

Pin Assignments
 Front View 前視圖

Pin Out

| | |
|-----------|-------|
| UNIT:mm | |
| TOLERANCE | |
| .X | ±0.25 |
| .XX | ±0.15 |
| .XXX | ±0.05 |
| ANGLES | ±1° |

| | |
|-------------------------------|----------------------------|
| Description | |
| M15 Distributor 1*4 In Series | |
| SCALE: N/A | SHEET 1 OF 1 |
| REV. D1 | SIZE A4 * :Inspection Item |



| | |
|----------|-------------|
| PART NO | 48002010-03 |
| DWG NO | |
| CUSTOMER | |

| | |
|-------------|------------|
| DRAWN BY | XuXianMing |
| CHECKED BY | |
| APPROVED BY | |

| | |
|------|----------|
| DATE | 20140514 |
| DATE | |
| DATE | |

| Material List | | | |
|---------------|--------------|------|----------------------------------|
| No. | Material No. | Q'ty | Material Description |
| 1 | 501-00062-00 | 4 | O-Ring Φ13*Φ9.0*Φ2.0 Silicon Gel |
| 2 | 104-00145-00 | 4 | Connector 2Pin,Nylon+GF |
| 3 | 107-00036-00 | 4 | Nut-02 (blue) |
| 4 | 801-00044-02 | 8 | ZnI.5 Brass 4u" Gold Plated |
| 5 | 903-00079-00 | 1 | PCB 1*4 , series FR-4, 94-V0 |
| 6 | 601-00040-00 | | Molding, Nylon (black) CHOGORI |
| 7 | 502-00010-00 | 1 | Gasket |
| 8 | 109-00004-00 | 1 | 103 Seals Nut |

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.