


Specifications
 Current Rating:3Amp
 Insulation Resistance:1000MΩMin.
 Dielectric Withstanding Voltage:600VAC
 Contact Resistance:20mΩMax.
 Operating Temperature:-40°C to +105°C
 Materials
 Contact Material:Phosphor Bronze
 Insulator Material:Polyester,UL 94V-0
 PA 6T or the
 equivalent material

ROHS COMPLIANT

Recommended P.C.Board
 Layout
 (Tolerance:±0.05)



Ordering Information

LEDT - XX XX

No. of Pins Per Row 02
 Standard Plating 01=Gold Flash, 02=Gold 30", 11=Tin, XX=Select Plating
 Packing T=Tube, TP=Tape+Reel 1

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN DATE	ELETE TECHNOLOGY CO., LTD 億溙得股份有限公司	
X. ±	X° ±5°	Andy2005. 08. 12	FILE NAME (品名)	LED Connector Male
.X ±0.38	.X° ±2°	CHECK DATE	PART NO (料号)	LEDM2-XXXXXXXLBX
.XX ±0.25	.XX° ±1°	APPRO. DATE	DRAWING NO.(图号)	LEDM2-05
.XXX ±0.13	.XXX° ±0.5°			REV.A0
UNIT:mm	SCALE 1:1			
A4	SHEET: 1 of 1			