6A05 THRU 6A10


GENERAL PURPOSE PLASTIC SILICON RECTIFIERS Reverse Voltage – 50 to 1000 V Forward Current – 6 A

Features

• High surge current capability

Mechanical Data

- Case: Molded plastic, R-6
- Epoxy: UL 94V-0 rate flame retardant
- Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- Polarity: Color band denotes cathode end
- Mounting Position: Any



Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half-wave, 60 Hz, resistive or inductive load, for capacitive load, derate current by 20%.

Parameter	Symbols	6A05	6A1	6A2	6A4	6A5	6A6	6A8	6A10	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	500	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	350	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	500	600	800	1000	V
Maximum Average Forward Rectified Current 0.375" (9.5 mm) Lead Length at $T_A = 60 ^\circ\text{C}$	I _{F(AV)}	6								A
Peak Forward Surge Current 8.3 ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	400								A
Maximum Forward Voltage at 6 A	V _F	1.1							V	
Maximum Reverse Current $T_A = 25 ^{\circ}C$ at Rated DC Blocking Voltage $T_A = 100 ^{\circ}C$	I _R	10 1000								μA
Typical Junction Capacitance ¹⁾	CJ	150							pF	
Typical Thermal Resistance ²⁾	$R_{ ext{ heta}JA}$	10								°C/W
Operating Junction Temperature Range	Tj	- 55 to + 150								°C
Storage Temperature Range	T _{stg}	- 55 to + 150								°C

¹⁾ Measured at 1 MHz and applied reverse voltage of 4 V D.C.

²⁾ Thermal resistance from junction to ambient 0.375"(9.5 mm) lead length P.C.B mounted with 1.1 X 1.1" (30 X 30 mm) copper pads.


SEMTECH ELECTRONICS LTD.


(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)






Dated : 18/04/2007 H











FIG. 4 - TYPICAL REVERSE CHARACTERISTICS









Dated : 18/04/2007 H