
1.5A SINGLE-PHASE SILICON BRIDGE RECTIFIERS Reverse Voltage – 50 to 1000 Volts Forward Current – 1.5 Amperes

Features

- Surge overload rating 50 amperes peak
- Ideal for printed circuit boards
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- Mounting Position: Any



Absolute Maximum Ratings and Characteristics

Ratings at 25°Cambient temperature unless otherwise specified. Single-phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

	Symbols	W005	W01	W02	W04	W06	W08	W10	Units
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	٧
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	800	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at $T_A = 25$ $^{\circ}C$	I _(AV)	1.5							А
Peak forward surge current , 8.3mS single half sine-wave superimposed on rated load	I _{FSM}	50							А
Rating for fusing (t<8.35ms)	l ² t	5						A ² t	
Maximum forward voltage drop per element at 1A peak	V _F	1							V
Maximum reverse current at rated $T_A = 25$ °C DC blocking voltage per element $T_A = 100$ °C	I _R	10 1.0							μA mA
Operating temperature range	TJ	-50 to +125							оС
Storage temperature range	T _A	-50 to +150							оС



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, acompany listed on the Hong Kong Stock Exchange, Stock Code: 724)







Dated : 03/12/2002

RATING AND CHARACTERISTICS CURVES








FIG. 2-DERATING CURVE **OUTPUT RECTIFIED CURRENT**




NUMBER OF CYCLES AT 60Hz

FIG. 3-TYPICAL FORWARD **CHARACTERISTICS**



INSTANTANEOUS FORWARD VOLTAGE, VOLTS

FIG. 4-TYPICAL REVERSE **CHARACTERISTICS**



PERCENT OF RATED PEAK REVERSE VOLTAGE



SEMTECH ELECTRONICS LTD.









Dated: 03/12/2002