





- 1.Maximum Electric Rating:105℃ 600V
2.Maximum Electric Current:22-16AWG/0.5-1.5mm²:19A
16-14AWG/1.5-2.5mm²:27A
12-10AWG/4-6mm²:48A
- 3.Terminal Bopper
4.Insulation:Nylon
5.Plating:Tin

BEISIT NO.	WireRange mm ² /Awg	TYPE	螺柱規格		DIMENSION							Insula- tion Color
			Stud Size	d2	W	F	L	E	D	d1	T	
					mm	mm	mm	mm	mm	mm	mm	
BT012-079	0.5~1.5 mm ² A.W.G 22~16	N-RV 1.25-3	#4	3.2(.126)	5.5(.216)	5.0(.197)	18.0(.709)	10.5(.413)	4.1(.161)	1.7(0.67)	0.75(0.30)	red
BT012-080		N-RVS 1.25-3.5	#6	3.7(.146)	6.6(.260)	6.3(.248)	20.1(.791)					
BT012-081		N-RVM 1.25-3.5	#6	3.7(.146)	5.5(.216)	5.0(.197)	18.0(.709)					
BT012-082		N-RVL 1.25-3.5	#6	3.7(.146)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-083		N-RVS 1.25-4	#8	4.3(.169)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-084		N-RVL 1.25-4	#8	4.3(.169)	6.6(.260)	6.3(.248)	20.1(.791)					
BT012-085		N-RVS 1.25-5	#10	5.3(.209)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-086		N-RVL 1.25-5	#10	5.3(.209)	8.0(.209)	7.0(.276)	21.5(.847)					
BT012-087		N-RV 1.25-6	1 / 4	6.4(.252)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-088		N-RV 1.25-8	5/16	8.4(.331)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-089		N-RV 1.25-10	3/8	10.0(.393)	14.0(.551)	14.5(.571)	32.0(1.22)					
BT012-090	1.5~2.5 mm ² A.W.G 16~14	N-RV 2-3	#4	3.2(.126)	6.6(.261)	6.3(.248)	20.6(.811)	11.0(.433)	4.5(.177)	2.3(.090)	0.8(.031)	blue
BT012-091		N-RVS 2-3.5	#6	3.7(.146)	6.6(.261)	6.3(.248)	20.6(.811)					
BT012-092		N-RVL 2-3.5	#6	3.7(.146)	8.0(.315)	7.0(.276)	22.0(.867)					
BT012-093		N-RVS 2-4	#8	4.3(.169)	8.0(.315)	7.0(.276)	22.0(.867)					
BT012-094		N-RVL 2-4	#8	4.3(.169)	9.5(.374)	7.3(.287)	22.8(.898)					
BT012-095		N-RV 2-5	#10	5.3(.209)	8.0(.315)	7.0(.276)	22.0(.867)					
BT012-096		N-RV 2-6	1 4	6.4(.252)	11.6(.457)	11.0(.433)	27.7(1.091)					
BT012-097		N-RV 2-8	5/16	8.4(.331)	11.6(.457)	11.0(.433)	27.7(1.091)					
BT012-098		N-RV 2-10	3/8	10.0(.393)	14.0(.551)	14.5(.571)	32.0(1.24)					
BT012-099		N-RV 5.5-3.5	#6	3.7(.146)	7.2(.283)	6.1(.240)	23.2(.914)					
BT012-100	4~6 mm ² A.W.G 12~10	N-RVS 5.5-4	#8	4.3(.169)	9.5(.374)	8.3(.327)	26.3(1.036)	13.5(.531)	6.5(.256)	3.4(.134)	1.0(.039)	yellow
BT012-101		N-RVL 5.5-4	#8	4.3(.169)	7.2(.283)	6.1(.240)	23.2(.914)					
BT012-102		N-RV 5.5-5	#10	5.3(.209)	9.5(.374)	8.3(.327)	26.3(1.036)					
BT012-103		N-RV 5.5-6	1 4	6.4(.252)	12.0(.472)	10.5(.413)	29.5(1.162)					
BT012-104		N-RV 5.5-8	5/16	8.4(.331)	15.0(.591)	13.5(.534)	34.7(1.366)					
BT012-105		N-RV 5.5-10	3/8	10.0(.393)	15.0(.591)	13.5(.534)	34.7(1.366)					
BT012-106		N-RV 5.5-12	1 2	13.0(.512)	19.0(.748)	16.0(.630)	39.0(1.536)					



- 1.Maximum Electric Rating:105℃ 600V
2.Maximum Electric Current:22-16AWG/0.5-1.5mm²:19A
16-14AWG/1.5-2.5mm²:27A
12-10AWG/4-6mm²:48A
- 3.Terminal Bopper
4.Insulation:Nylon
5.Plating:Tin

BEISIT NO.	WireRange mm ² /Awg	TYPE	螺柱規格		DIMENSION							Insula- tion Color
			Stud Size	d2	W	F	L	E	D	d1	T	
					mm	mm	mm	mm	mm	mm	mm	
BT012-107	0.5~1.5 mm ² A.W.G 22~16	N-RV 1.25-3	#4	3.2(.126)	5.5(.216)	5.0(.197)	18.0(.709)	10.5(.413)	4.5(.177)	1.7(0.67)	0.8(0.31)	red
BT012-108		N-RVS 1.25-3.5	#6	3.7(.146)	6.6(.260)	6.3(.248)	20.1(.791)					
BT012-109		N-RVM 1.25-3.5	#6	3.7(.146)	5.5(.216)	5.0(.197)	18.0(.709)					
BT012-110		N-RVL 1.25-3.5	#6	3.7(.146)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-111		N-RVS 1.25-4	#8	4.3(.169)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-112		N-RVL 1.25-4	#8	4.3(.169)	6.6(.260)	6.3(.248)	20.1(.791)					
BT012-113		N-RVS 1.25-5	#10	5.3(.209)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-114		N-RVL 1.25-5	#10	5.3(.209)	8.0(.209)	7.0(.276)	21.5(.847)					
BT012-115		N-RV 1.25-6	1 / 4	6.4(.252)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-116		N-RV 1.25-8	5/16	8.4(.331)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-117		N-RV 1.25-10	3/8	10.0(.393)	14.0(.551)	14.5(.571)	32.0(1.22)					
BT012-118	1.5~2.5 mm ² A.W.G 16~14	N-RV 2-3	#4	3.2(.126)	6.6(.261)	6.3(.248)	20.1(.791)	11.0(.433)	5.2(.205)	2.3(.091)	0.8(.031)	blue
BT012-119		N-RVS 2-3.5	#6	3.7(.146)	6.6(.261)	6.3(.248)	20.1(.791)					
BT012-120		N-RVL 2-3.5	#6	3.7(.146)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-121		N-RVS 2-4	#8	4.3(.169)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-122		N-RVL 2-4	#8	4.3(.169)	6.6(.374)	6.3(.248)	20.1(.791)					
BT012-123		N-RVS 2-5	#10	5.3(.209)	9.5(.374)	7.3(.287)	21.8(.858)					
BT012-124		N-RVL 2-5	#10	5.3(.209)	8.0(.315)	7.0(.276)	21.5(.847)					
BT012-125		N-RV 2-6 /	1 4	6.4(.252)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-126		N-RV 2-8	5/16	8.4(.331)	11.6(.457)	11.0(.433)	27.2(1.071)					
BT012-127		N-RV 2-10	3/8	10.0(.393)	14.0(.551)	14.5(.571)	32.0(1.24)					
BT012-128	4~6 mm ² A.W.G 12~10	N-RV 5.5-3.5	#6	3.7(.146)	7.2(.283)	6.1(.240)	23.2(.914)	13.0(.512)	7.0(.276)	3.5(.137)	1.0(.039)	yellow
BT012-129		N-RVS 5.5-4	#8	4.3(.169)	9.5(.374)	8.3(.327)	25.8(1.016)					
BT012-130		N-RVL 5.5-4	#8	4.3(.169)	7.2(.283)	6.1(.240)	23.3(.914)					
BT012-131		N-RV 5.5-5	#10	5.3(.209)	9.5(.374)	8.3(.327)	26.2(1.036)					
BT012-132		N-RV 5.5-6 /	1 4	6.4(.252)	12.0(.472)	10.5(.413)	29.5(1.162)					
BT012-133		N-RV 5.5-8	5/16	8.4(.331)	15.0(.591)	13.5(.534)	34.7(1.366)					
BT012-134		N-RV 5.5-10	3/8	10.0(.393)	15.0(.591)	13.5(.534)	34.7(1.366)					
BT012-135		N-RV 5.5-12 /	1 2	13.0(.512)	19.0(.748)	16.0(.630)	39.0(1.536)					