



Conductor section:0.5-1.5mm²(A.W.G22~ 16) I_{max}=19A Material: Copper Thickness:0.7mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					color
				B	L	F	H	Dφ	
				mm	mm	mm	mm	mm	
BT012-136	SV 1.25-3	# 4	3.2	5.7	21.2	6.5	10	4.3	red
BT012-137	SVS 1.25-3.5	# 6	3.7	5.7	21.2	6.5			
BT012-138	SVL 1.25-3.5	# 6	3.7	6.4	21.2	6.5			
BT012-139	SVS 1.25-4	# 8	4.3	6.4	21.2	6.5			
BT012-140	SVM 1.25-4	# 8	4.3	7.2	21.2	6.5			
BT012-141	SVL 1.25-4	# 8	4.3	8.1	21.2	6.5			
BT012-142	SVS 1.25-5	# 10	5.3	8.1	21.2	6.5			
BT012-143	SVL 1.25-5	# 10	5.3	9.5	21.2	6.5			
BT012-144	SVS 1.25-6	1/4	6.4	9.5	21.2	6.5			
BT012-145	SVL 1.25-6	1/4	6.4	12.0	27.2	11.0			

Conductor section:0.5-1.5mm²(A.W.G16~ 14) I_{max}=27A Material: Copper Thickness:0.8mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					color
				B	L	F	H	Dφ	
				mm	mm	mm	mm	mm	
BT012-146	SV 2-3	# 4	3.2	5.7	21.2	6.5	10	4.9	blue
BT012-147	SVS 2-3.5	# 6	3.7	5.7	21.2	6.5			
BT012-148	SVL 2-3.5	# 6	3.7	6.4	21.2	6.5			
BT012-149	SVS 2-4	# 8	4.3	6.0	21.2	6.5			
BT012-150	SVM 2-4	# 8	4.3	7.2	21.2	6.5			
BT012-151	SVL 2-4	# 8	4.3	8.1	21.2	6.5			
BT012-152	SVS 2-5	# 10	5.3	8.1	21.2	6.5			
BT012-153	SVL 2-5	# 10	5.3	9.5	21.2	6.5			
BT012-154	SVS 2-6	1/4	6.4	9.5	21.2	6.5			
BT012-155	SVL 2-6	1/4	6.4	12.0	27.2	11.0			

Conductor section:2.5-4mm²(A.W.G14~ 12) I_{max}=37A Material: Copper Thickness:1.0mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					color
				B	L	F	H	Dφ	
				mm	mm	mm	mm	mm	
BT012-156	SV 3.5-3	#4	3.2		24.8	7.0	13.0	6.2	black
BT012-157	SV 3.5-4	#8	4.3		24.8	7.0			
BT012-158	SV 3.5-5	#10	5.3		24.8	7.0			
BT012-159	SV 3.5-6	1/4	6.4		28.0	12.1			

Conductor section:4-6mm²(A.W.G12~ 10) I_{max}=48A Material: Copper Thickness:1.0mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					color
				B	L	F	H	Dφ	
				mm	mm	mm	mm	mm	
BT012-160	SV 5.5-3.5	# 6	3.7	8.3	26	7.5	13.0	6.7	yellow
BT012-161	SVS 5.5-4	# 8	4.3	8.3	26	7.5			
BT012-162	SVL 5.5-4	# 8	4.3	9.0	26	7.5			
BT012-163	SV 5.5-5	# 10	5.3	9.0	26	7.5			
BT012-164	SVS 5.5-6	1/4	6.4	9.0	26	7.5			
BT012-165	SVL 5.5-6	1/4	6.4	12.0	32	12.0			
BT012-166	SV 5.5-8	5/16	8.4	14.0	37	11.5			



Conductor section:0.5-1.5mm²(A.W.G22~ 16) I_{max}=19A Material: Copper Thickness:0.7mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					
				B	L	F	E	Dφ	d φ
				mm	mm	mm	mm	mm	mm
BT012-167	SNB 1.25-3	# 4	3.2	5.7	16.0	6.5	4.8	3.4	1.7
BT012-168	SNBS 1.25-3.5	# 6	3.7	5.7	16.0	6.5			
BT012-169	SNBL 1.25-3.5	# 6	3.7	6.4	15.5	6.5			
BT012-170	SNBS 1.25-4	# 8	4.3	6.4	15.5	6.5			
BT012-171	SNBM 1.25-4	# 8	4.3	7.2	15.5	6.5			
BT012-172	SNBL 1.25-4	# 8	4.3	8.1	15.5	6.5			
BT012-173	SNBS 1.25-5	# 10	5.3	8.1	15.5	6.5			
BT012-174	SNBL 1.25-5	# 10	5.3	9.5	15.5	6.5			
BT012-175	SNBS 1.25-6	1/4	6.4	9.5	15.5	6.5			
BT012-176	SNBL 1.25-6	1/4	6.4	12.0	22.0	11.0			

Conductor section:1.5-2.5mm²(A.W.G16~ 14) I_{max}=27A Material: Copper Thickness:0.8mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					
				B	L	F	E	Dφ	d φ
				mm	mm	mm	mm	mm	mm
BT012-177	SNB 2-3	# 4	3.2	5.7	16.0	6.5	4.8	4.1	2.3
BT012-178	SNBS 2-3.5	# 6	3.7	5.7	16.0	6.5			
BT012-179	SNBL 2-3.5	# 6	3.7	6.0	16.0	6.5			
BT012-180	SNBS 2-4	# 8	4.3	6.4	16.0	6.5			
BT012-181	SNBM 2-4	# 8	4.3	7.2	16.0	6.5			
BT012-182	SNBL 2-4	# 8	4.3	8.1	16.0	6.5			
BT012-183	SNBS 2-5	# 10	5.3	8.1	16.0	6.5			
BT012-184	SNBL 2-5	# 10	5.3	9.5	16.0	6.5			
BT012-185	SNBS 2-6	1/4	6.4	9.5	16.0	6.5			
BT012-186	SNBL 2-6	1/4	6.4	12.0	22.0	11.0			

Conductor section:2.5-4mm²(A.W.G14~ 12) I_{max}=37A Material: Copper Thickness:1.0mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					
				B	L	F	E	Dφ	d φ
				mm	mm	mm	mm	mm	mm
BT012-187	SNB 3.5-3	# 4	3.2	5.7	18.3	7.0	6.0	5.0	3.0
BT012-188	SNB 3.5-4	# 8	4.3	8.0	18.3	7.0			
BT012-189	SNB 3.5-5	# 10	5.3	8.0	18.3	7.0			
BT012-190	SNB 3.5-6	1/4	6.4	12.0	21.5	10.5			

Conductor section:4-6mm²(A.W.G12~ 10) I_{max}=48A Material: Copper Thickness:1.0mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					
				B	L	F	E	Dφ	d φ
				mm	mm	mm	mm	mm	mm
BT012-191	SNB 5.5-3.5	#6	3.7	8.3	19.5	7.2	6.8	5.6	3.4
BT012-192	SNBS 5.5-4	#8	4.3	8.3	19.5	7.2			
BT012-193	SNBL 5.5-4	#8	4.3	9.0	19.5	7.5			
BT012-194	SNB 5.5-5	#10	5.3	9.0	19.5	7.5			
BT012-195	SNBS 5.5-6	1/4	6.4	9.0	19.5	7.2			
BT012-196	SNBL 5.5-6	1/4	6.4	12.0	25.5	12.0			
BT012-197	SNB 5.5-8	5/16	8.4	14.0	24.5	11.5			

Material: copper Thickness:1.2mm、1.4mm、1.7mm

BEISIT NO.	TYPE	American Bolt number	d2φ (mm)	DIMENSION					
				B	L	F	E	Dφ	d φ
				mm	mm	mm	mm	mm	mm
BT012-198	SNB 8-4	#8	4.3	8.7	23.0	6.0	8.5	7.2	4.5
BT012-199	SNB 8-5	#10	5.3	12.0	24.5	5.7	8.5	7.2	4.5
BT012-200	SNB 8-6	1/4	6.4	12.0	24.5	5.7	8.5	7.2	4.5
BT012-201	SNB 8-8	5/16	8.4	14.5	28.0	8.3	8.5	7.2	4.5
BT012-202	SNB 14-6	1/4	6.4	12.0	28.0	7.5	10.5	9.0	5.8
BT012-203	SNB 14-8	5/16	8.4	14.0	28.0	7.5	10.5	9.0	5.8
BT012-204	SNB 22-8	5/16	8.4	14.0	34.5	9.0	12.0	11.5	7.7

