PARA					
PARAMETER		SPECIFICATION			
Coil former material		phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481			
Pin material		copper-tin alloy (CuSn), tin (Sn) plated			
Maximum operating temperature		180°C, "IEC 60085", class H			
Resistance to soldering heat		"IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s			
Soldeerability		"IEC 60068-2-20", Part 2, Test Ta, method 1			
		- 7.50 -		000 +	
	+	j 			
Winding data a	and area product		6/7.2 coil forme	er	
Winding data a NUMBER OF SECTIONS			6/7.2 coil forme AVERAGE LENGTH OF TURN (mm)	AREA	TYPE NUMBER
NUMBER OF	and area product WINDING AREA	for 8-pins EF1 MINIMUM WINDING WIDTH	AVERAGE LENGTH OF TURN	AREA PRODUCT Ae x Aw	TYPE NUMBER EF-1606-1S-8P
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<l≤<br="">16<l≤45±0.30 45<="" td=""><td>and area product WINDING AREA (mm²) 16</td><td>for 8-pins EF1 MINIMUM WINDING WIDTH (mm) 6.00</td><td>AVERAGE LENGTH OF TURN (mm) 40</td><td>AREA PRODUCT Ae x Aw (mm⁴) 455</td><td></td></l≤45±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 16	for 8-pins EF1 MINIMUM WINDING WIDTH (mm) 6.00	AVERAGE LENGTH OF TURN (mm) 40	AREA PRODUCT Ae x Aw (mm ⁴) 455	
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<l≤<br="">16<l≤4±0.30 45<br="">Pin Dim:±0.05 Thio</l≤4±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 16	for 8-pins EF1 MINIMUM WINDING WIDTH (mm) 6.00 Dimer (m h:±0.20	AVERAGE LENGTH OF TURN (mm) 40	AREA PRODUCT Ae x Aw (mm ⁴) 455	EF-1606-1S-8P MARK Bobbin material: T385J
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<l≤<br="">16<l≤4±0.30 45<br="">Pin Dim:±0.05 Thio</l≤4±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 16	for 8-pins EF1 MINIMUM WINDING WIDTH (mm) 6.00 Dimer (m h:±0.20	AVERAGE LENGTH OF TURN (mm) 40 Mould No. Code No.: 2tronics 4-87693589	AREA PRODUCT Ae x Aw (mm ⁴) 455 RE FAY01091	EF-1606-1S-8P MARK Bobbin material: T385J Available for Fuan core: EF16/7.2

COIL FORMER General data 8-pins EF16/7.2 coil former